



Signalink SL-1+

Specifications:

Power Supply: 6.75 - 15 Volts DC @ 13 ma (nominal)
Freq Response: 100Hz - 30KHz
In/Out Impedance: 600 Ohm (nom)
Attenuation: Radio to Sound Card - Adjustable
Sound Card to Radio - Adjustable
Auto-PTT™ Delay: Fast - 28 milliseconds
Variable - 300 ms to 3 seconds
PTT Circuit: MOSFET Transistor
Rating - 15 Volts @ 75ma (max)
Radio Connector: Mic, Spkr, Pwr, PTT - RJ-45
Spkr - 3.5mm Mono
Sound Card Conn: Mic Input - 3.5mm Stereo
Spkr Output - 3.5mm Stereo
Other Connectors: Aux. Spkr - 3.5mm Mono
Aux. Power - 2.1mm Coaxial
Case: Extruded Aluminum - 6061T4
Dimensions: 1.1" x 2.7" x 3.2"
Operating Temp: -30C to +60C

- **No Serial or USB Port Required**
- **Complete Radio Isolation**
- **Adjustable Rx & Tx Levels**
- **Variable Transmit Delay**
- **Works with ALL Radios**
- **Uses Mic, Data, or Accy Port**
- **Supports All Available Digital and Voice Modes**